

Suppression Mesh | 120"

A technologically advanced ceiling fabric made from 100% IFR Polyester fiber in a mesh construction has 1/4" holes and a cover factor of 66%. Its exclusive water transport system maximizes sprinkler flow through the fabric.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Raw Material			100% Polyester
Coating			None
Weight		148g/sq.m	4.33oz./sq.yd.
Construction			Knit
Stretch			5%L X 5%W
Roll Size		Approx. 91 m	Approx. 100 yds.
Fire Classification	NFPA701Sm, CA1237Sm		
Suggested Temp Speed			375° - 410° 1-2 Min

Applications

Ceilings	Theatrical	Banners Indoors	Banners Outdoor	Pop-Up	Light Boxes	Flags	Trade Show	Signage
X							X	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Dye-Sub Transfer	Dye-Sub Direct
				X	

Available Sizes

Metric (m)	English (inches)
3.05 m	120"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

California
10671 Lorne St.
Sun Valley, CA 91352
877-432-9426

Florida
7100 TPC Drive, Suite 650
Orlando, FL 32822
888-318-2904

New Jersey
18 Central Blvd.
South Hackensack, NJ 07606
877-232-9426

info@dazian.com | www.dazian.com