

Trapeze® Plus | 122"

Trapeze® Plus set the industry standard for tension fabric performance and expectations both here and abroad. Made from inherently flame retardant polyester, this fabric has been engineered for durability and high performance. It has a 3-way stretch of 80% length by 50% width by 50% diagonal, producing superior tension graphics.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Raw Material			10% Spandex 90% Polyester
Coating			None
Weight		200g/sq.m	5.9oz./sq.yd.
Construction			Knit
Stretch			80%L X 50%W X 50%Dia.
Roll Size		Approx. 91 m	Approx. 100 yds.
Fire Classification	NFPA701Sm, CA1237Sm, B1		
Suggested Temp Speed			375° - 400° 1-2 Min

Applications

Ceilings	Theatrical	Banners Indoors	Banners Outdoor	Pop-Up	Light Boxes	Flags	Trade Show	Signage
	X	X		X			X	X

Ink Printability

Solvent	Eco Solvent	UV	Latex	Dye-Sub Transfer	Dye-Sub Direct
				X	

Available Sizes

Metric (m)	English (inches)
3.1 m	122"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

California
10671 Lorne St.
Sun Valley, CA 91352
877-432-9426

Florida
7100 TPC Drive, Suite 650
Orlando, FL 32822
888-318-2904

New Jersey
89 Leuning St. Unit D2
South Hackensack, NJ 07606
877-232-9426

info@dazian.com | www.dazian.com