

### Selene | 126"

A medium weight, tightly woven backlit fabric with a light diffusing acrylic coating. Delivers vivid, evenly illuminated backlit imagery.

#### Material Details

| CHARACTERISTICS          | TEST METHOD                  | METRIC       | ENGLISH         |
|--------------------------|------------------------------|--------------|-----------------|
| Raw Material             |                              |              | 100% Polyester  |
| Coating                  |                              |              | Acrylic         |
| Weight                   |                              | 170g/sq.m    | 5.2oz./sq.yd.   |
| Construction             |                              |              | Woven           |
| Stretch                  |                              |              | N/A             |
| Roll Size                |                              | Approx. 50 m | Approx. 55 yds. |
| Fire Classification      | FR                           |              |                 |
| Fire Class When Treated* | NFPA 701, Title 19 (CA 1237) |              |                 |
| Suggested Temp   Speed   |                              |              |                 |

#### Applications

| Ceilings | Theatrical | Banners<br>Indoors | Banners<br>Outdoor | Pop-Up | Light Boxes | Flags | Trade Show | Signage |
|----------|------------|--------------------|--------------------|--------|-------------|-------|------------|---------|
|          |            |                    |                    |        | X           |       | X          | X       |

#### Ink Printability

| Solvent | Eco<br>Solvent | UV | Latex | Dye-Sub<br>Transfer | Dye-Sub<br>Direct |
|---------|----------------|----|-------|---------------------|-------------------|
|         |                | X  | X     |                     | X                 |

#### Size

| Metric (m) | English (inches) |
|------------|------------------|
| 3.2 m      | 126"             |

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

**California**  
10671 Lorne St.  
Sun Valley, CA 91352  
877-432-9426

**Florida**  
7100 TPC Drive, Suite 650  
Orlando, FL 32822  
888-318-2904

**New Jersey**  
89 Leuning St. Unit D20  
South Hackensack, NJ 07606  
877-232-9426

info@dazian.com | www.dazian.com