

Softimage 240 | 122" + 199"

A medium weight Polyester knit with a poplin construction. The backside has a Polyurethane direct print coating.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Raw Material			100% Polyester
Coating			Ink Jet PU
Weight		255g./sq.m.	7.6oz./sq.yd.
Construction			Knit
Stretch			1% - 2%
Roll Size		Approx. 50 m	Approx. 55 yds.
Fire Classification	Bs-1, M-1, NFPA701Sm		
Suggested Temp Speed			410° 50 Seconds

Applications

Ceilings	Theatrical	Banners Indoors	Banners Outdoor	Pop-Up	Light Boxes	Flags	Trade Show	Signage
	X	X		X			X	X

Ink Printability

Solvent	Eco Solvent	UV	Latex	Dye-Sub Transfer	Dye-Sub Direct
		X			X

Available Sizes

Metric (m)	English (inches)
3.1 m	122"
5.05 m	199"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

California
10671 Lorne St.
Sun Valley, CA 91352
877-432-9426

Florida
7100 TPC Drive, Suite 650
Orlando, FL 32822
888-318-2904

New Jersey
89 Leuning St. Unit D2
South Hackensack, NJ 07606
877-232-9426

info@dazian.com | www.dazian.com