

Technical Data Sheet

Evoke™ Trapeze® Plus | 122"

Trapeze® Plus set the industry standard for tension fabric performance and expectations both here and abroad. Made from a blend of GRS 4.0 Certified 100% Recycled Polyester and Spandex, this fabric has been engineered for durability and high-tension performance. It has a 3-way stretch of 80% length by 50% width by 50% diagonal, producing superior stretch graphics.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Raw Material			90% Recycled Polyester
			10% Spandex
Coating			None
Weight		200g/sq.m	5.9oz./sq.yd.
Construction			Knit
Stretch			80%L X 50%W X 50%Dia.
Roll Size		Approx. 91 m	Approx. 100 yds.
Recycled Bottles Per Yd	27		
Sustainable Certification	GRS 4.0		
Fire Classification	NFPA701Sm, CA1237Sm, B1		
Suggested Temp Speed		·	375° - 400° 1-2 Min

Applications

Ceilings		Banners Indoors	•	Light Boxes	Flags	Trade Show	Signage
	X	Х	X			Х	Х

Ink Printability

Solvent	Eco	UV	Latex	Dye-Sub	Dye-Sub
	Solvent			Transfer	Direct
				X	

Available Sizes

Metric (m)	English (inches)	
3.1 m	122"	

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

California

10671 Lorne St. Sun Valley, CA 91352 818-287-3800 Florida

7100 TPC Drive. Suite 650 Orlando, FL 32822 407-367-7616 **New Jersey**

89 Leuning St. Unit D2 South Hackensack, NJ 07606 201-549-1000

info@dazian.com | www.dazian.com

