

Technical Data Sheet

Evoke™ Suppression Mesh | 126"

A technologically advanced ceiling fabric made with GRS 4.0 Certified 100% Recycled Polyester fiber. It has a water-repellant coating, 1/4" holes, and a cover factor of 66%. Its exclusive water transport system maximizes sprinkler flow through the fabric and reduces water absorbency. Available In White and Black.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Raw Material			100% Recycled Polyester
Coating			None
Weight		148g/sq.m	4.33oz./sq.yd.
Construction			Knit
Stretch			10%L X 20%W
Roll Size		Approx. 91 m	Approx. 100 yds.
Recycled Bottles Per Yd.	27		
Sustainable Certification	GRS 4.0		
Fire Classification	NFPA701Sm CA1237Sm		
	B1		
Suggested Temp Speed			375° - 410° 1-2 Min

Applications

Ceilings	Theatrical	Banners Indoors		Light Boxes	Flags	Trade Show	Signage
X						Х	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Dye-Sub Transfer	Dye-Sub Direct
				X	

Available Sizes

Metric (m)	English (inches)
3.2 m	126"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

California 10671 Lorne St. Sun Valley, CA 91352 818-287-3800 Florida 7100 TPC Drive. Suite 650 Orlando, FL 32822 407-367-7616 New Jersey 89 Leuning St. Unit D2 South Hackensack, NJ 07606 201-549-1000

info@dazian.com | www.dazian.com

