



ProjectTex™ Projection Fabrics

DAZIAN

Fabric	Color	Width(s)	FL: 0°	FC: 0°	Gain: 0°	FL: 30°	FC: 30°	Gain: 30°	FP	RP	Fabric Description
ProjecTex™ Assimilator Spacer	White	120"	23.12	31.92	0.72	22.87	31.92	0.71	X		Designed For High Impact Sport Training & Gaming Assimilators
ProjecTex™ Selene	White	126" 199"	27.25	31.92	0.87	24.13	31.92	0.31	X	X	Polyurethane Light Diffusing Coating Moderate Creasing
ProjecTex™ Celtic Black Back	White/Black	126"	28.49	31.92	0.89	26.54	31.92	0.83	X		White Front – Black Back Black Blackout Acrylic Coating
ProjecTex™ Celtic Black Back	White/Black	199"	28.49	31.92	0.89	26.54	31.92	0.83	X		White Front – Black Back Black Blackout Acrylic Coating
ProjecTex™ Trevira Muslin	White	20' 32'9"	21.53	31.92	0.67	19.17	31.92	0.60	X	X	100% Polyester Ideal For Wide-Width Seamless Screens
ProjecTex™ Cotton Scenery Muslin	White	126" 14' 33' 40'	22.55	31.92	0.71	21.75	31.92	0.68	X	X	Heavyweight Tightly Woven Optimal Opacity Great For Large Seamless Screens + Cycs
ProjecTex™ Poly Spun	White	124"	21.20	31.92	0.66	18.17	31.92	0.57	X	X	100% Polyester Anti-Wrinkle Properties
ProjecTex™ Poly Spun	Feather Grey	124"	19.23	31.92	0.66	16.94	31.92	0.53	X	X	100% Polyester Anti-Wrinkle Properties
ProjecTex™ Poly Spun	Storm Grey	124"	16.12	31.92	0.50	15.22	31.92	0.47	X	X	100% Polyester Anti-Wrinkle Properties
ProjecTex™ Poly Spun	Black	124"	10.86	31.92	0.34	11.52	31.92	0.36	X	X	100% Polyester Anti-Wrinkle Properties

Fabric	Color	Width(s)	FL: 0°	FC: 0°	Gain: 0°	FL: 30°	FC: 30°	Gain: 30°	FP	RP	Fabric Description
ProjecTex™ Trapeze Plus	White	122"	18.94	31.92	0.59	18.02	31.92	0.56	X	X	3-Way Stretch High Performance & Durability
ProjecTex™ Trapeze Plus	Contrast Grey	122"	16.66	31.92	0.52	15.42	31.92	0.48	X	X	3-Way Stretch High Performance & Durability
ProjecTex™ Trapeze Plus	Titanium	122"	13.88	31.92	0.43	14.37	31.92	0.45	X	X	3-Way Stretch High Performance & Durability
ProjecTex™ Trapeze Plus HW	White	122"	23.21	31.92	0.73	21.43	31.92	0.67	X	X	Excellent Stretch Recovery Wrinkle Resistant
ProjecTex™ Acrobat® w/MIRA-S™	White	120"	19.34	31.92	0.61	18.76	31.92	0.58	X	X	Excellent Stretch Recovery Balanced Length & Width Stretch UV Fastness For Temporary Outdoor Use
ProjecTex™ Acrobat® HV w/MIRA-S™	White	120"	24.11	31.92	0.78	22.03	31.92	0.72	X	X	HW Stretch Superior Elasticity & Softness UV Fastness For Temporary Outdoor Use
ProjecTex™ Sharkstooth 2T	White	31'	13.96	31.92	0.44	13.04	31.92	0.41	X	X	95% Cotton / 5% Polyester Bleed-Through Imagery & Visual FX
ProjecTex™ Sharkstooth 2T	Black	31'	9.98	31.92	0.31	8.77	31.92	0.27	X	X	95% Cotton / 5% Polyester Bleed-Through Imagery & FX
ProjecTex™ Evoke™ Deauville Mesh	White	124"	14.28	31.92	0.45	13.82	31.92	0.43	X	X	Acrylic Coating Sound + Wind Pass-Through
ProjecTex™ Evoke™ Deauville Mesh	Black	124"	11.53	31.92	0.36	10.68	31.92	0.33	X	X	Acrylic Coating Sound + Wind Pass-Through

Fabric	Color	Width(s)	FL: 0°	FC: 0°	Gain: 0°	FL: 30°	FC: 30°	Gain: 30°	FP	RP	Fabric Description
ProjecTex™ 3D Celtic	White	126"	31.27	31.92	0.98	24.78	31.92	0.78	X		Triple Layer Construction Wrinkle Resistant
ProjecTex™ Celtic Cloth	White	126"	20.80	31.92	0.65	20.65	31.92	0.65	X	X	Moderate Stretch Soft Knit Wrinkle Resistant
ProjecTex™ Celtic Cloth	Contrast Grey	126"	18.88	31.92	0.56	17.31	31.92	0.54	X	X	Moderate Stretch Soft Knit Wrinkle Resistant
ProjecTex™ Celtic Cloth HW	White	126"	23.47	31.92	0.74	22.33	31.92	0.70	X	X	Moderate Stretch Heavy Knit Wrinkle Resistant
ProjecTex™ Celtic Cloth HW	Contrast Grey	126"	20.62	31.92	0.64	21.11	31.92	0.66	X	X	Moderate Stretch Heavy Knit Wrinkle Resistant
ProjecTex™ Celtic Cloth HW	Pewter	126"	16.71	31.92	0.52	16.22	31.92	0.50	X	X	Moderate Stretch Heavy Knit Wrinkle Resistant

Testing Conditions & Equipment Specifications

Projector: Panasonic PT-RZ470UK
 Lumens: 3500
 Room Ambient Light: 0.008 FL
 Light Meter: Sekonic L-858D-U
 Software: Datacolor Syder 5 Elite
 FL: Foot Lamberts
 FC: Foot Candles

Readings Taken 6' From Screen Surface.
 All Numbers Listed Are Based On FP Readings.
 Results May Vary.



www.dazian.com

CA: 818-287-3800 | FL: 321-206-0084 | NJ: 201-549-1000